


 Chain shackle with screw pin	Working Load Limit (tonnes)	Dia. Bow d (mm)	Dia. Pin D (mm)	Inside Width W (mm)	Inside Length		Width of Bow B (mm)	Approx. Weight Each	
					Chain Type L (mm)	Anchor Type L (mm)		Screw Pin (Kg)	Safety Pin (Kg)
 Anchor shackle with screw pin	0.33	5	6	10	-	22	15	0.02	-
	0.50	6	8	12	22	29	20	0.06	0.07
	0.75	8	10	13	26	31	21	0.11	0.13
	1.00	10	11	17	32	37	26	0.15	0.17
	1.50	11	13	18	37	43	29	0.21	0.25
	2.00	13	16	21	41	48	33	0.37	0.44
	3.25	16	19	27	51	61	43	0.65	0.79
 Safety chain shackle Bolt type	4.75	19	22	32	60	72	51	1.06	1.26
	6.50	22	25	37	71	84	58	1.56	1.88
	8.50	25	29	43	81	95	68	2.32	2.78
	9.50	29	32	46	90	108	74	3.28	3.87
	12.00	32	35	52	100	119	83	4.51	5.26
	13.00	35	38	57	113	133	92	5.43	6.94
	17.00	38	41	60	124	146	98	7.89	8.79
	25.00	44	51	73	146	178	127	13.40	14.99
	35.00	51	57	83	171	197	146	18.85	20.65
	45.00	57	63	95	181	222	160	26.06	29.01
 Safety anchor shackle Bolt type	55.00	63	70	105	203	267	184	37.86	41.05
	85.00	76	83	127	229	330	200	58.68	62.24
	120.00	89	95	146	267	381	241	-	110.0
	150.00	102	108	165	318	432	279	-	160.0